

Böcker



Top-Lift

The versatile Top-Lift of Böcker



- 1 Knee joint**
Adjustable from 20°– 45°. Heavy duty hardened steel pulleys for long life of rope.
- 2 Drive unit Top-Lift Basic**
Hoisting speed 25 m/min., suitable for standard and tilting carriage, maximum payload 150 kg.
- 3 Standard carriage**
For use when there is no need to tilt for unloading. A safety break device prevents the carriage from falling in the event of a rope failure.
- 4 Universal platform**
Used for the transport of shingles, roof tiles and slate.
- 5 Articulated base plates**
Perfect positioning due to articulated base. Also available as height adjustable base plates (optional).

- 1 Tilting carriage with tilting bucket for loose material**
Can be tilted at top and bottom.
- 2 Load carrying devices** are all easily attached to the standard or tilting carriage.
- 3 Rail sections**
2 m long, weighing 10 kg only. Maximum rail length 20.30 m.
- 4 Hand control with push buttons**
UP / DOWN / EMERGENCY STOP on 5 m long cable.
- 5 Drive unit Top-Lift Standard**
Hoisting speed 34 m/min., suitable for standard and tilting carriage, maximum payload 250 kg.
- 6 Rail support**
Extendable from 2 – 5.5 m, a second support is necessary for rail length exceeding 16 m.



1 Sheet platform for plasterboards etc. up to 1.50 m width.

2 Drive unit Top-Lift HighSpeed
Hoisting speeds 20 and 40 m/min., suitable for standard and tilting carriage, maximum payload 230 kg.

3 Tilting carriage
Tips the load at the head section or pivots to a comfortable unloading position (with broken rope device).

1 Top-Lift drive
Can also be used as a construction winch.

2 Swing arm
The lightweight swing arm with a dead weight of only 15 kg is quickly mounted at the desired scaffold level.

3 Overload safety device
Serves as attachment device and overload protection device.

4 Hook
Can be easily attached.

Technical Data & Accessories





tilting bucket 80 litre (for tilting carriage only)



sheet-platform 90 x 15 x 220 cm



solar-platform standard



uni-platform 60 x 35 x 85 cm with protection grating



uni-platform comfort 70 x 44 x 70 cm



platform 60 x 85 x 35 cm with side-flaps

Technical Data

Type	Top-Lift Basic	Top-Lift Standard	Top-Lift HighSpeed
Payload [kg]	150	250	230
Lifting speed [m/min]	25	34	20 / 40
Lifting height max. [m]	20,30	20,30	20,30
Rope length [m]	44	44	44
Rope diameter [mm]	5	6	6
Voltage [V / Hz]	230 / 50	230 / 50	230 / 50
Control voltage [V]	24	24	24
Weight of drive unit [kg]	47	54	54

Subject to change of dimensions and design.

Böcker – made in
 **GERMANY**



**DENSEST
SERVICE-NETWORK
IN EUROPE**

Toplift_102017

Böcker Belgium NV

Boomsesteenweg 101 · B-2630 Aartselaar
Fon +32 (0)3 4576241
Fax +32 (0)3 4576242
Mail info@boecker.be

Böcker France SAS

5, rue Maximilien Robespierre · F-93130 Noisy-le-Sec
Fon +33 (0)1 48406767
Fax +33 (0)1 48406768
Mail info@boecker.fr

Böcker Italia srl

Sede Legale:
Corso Porta Nuova 11 · IT-37122 Verona (VR)
Sede Operativa/Amministrativa:
Via delle Nazioni 6 · IT-37012 Bussolengo (VR)
Fon +39 045 8780399
Fax +39 045 8780420
Mail info@boecker.it

Böcker Nederland B.V.

De Geerden 22 · NL-5334 LE Velddriel
Fon +31 (0)418 571444
Fax +31 (0)418 635222
Mail info@boecker.nl

Böcker Schweiz AG

Industriestr. 17 · CH-4800 Zofingen
Fon +41 (0)62 7976262
Fax +41 (0)62 7976268
Mail info@boecker.ch

Böcker UK Ltd.

Unit B Grazebrook Park
Hulbert Drive · Dudley
West Midlands · UK-DY2 0XW
Fon +44 (0)1384 476580
Mail info@boecker.co.uk

Böcker

Böcker Maschinenwerke GmbH
Lippestraße 69–73 · D-59368 Werne
Fon +49 (0) 23 89 / 79 89-0
Fax +49 (0) 23 89 / 79 89-9000
Mail info@boecker-group.com